

Encon[®]
SAFETY PRODUCTS
1-800-283-6266
 phone: (713) 466-1449
 email: customerservice@enconsafety.com

**30 GPM STAINLESS STEEL
 SHOWER HEAD**
PART NUMBER: 01055007

SPECIFICATION:

Shower head shall provide a non-injurious stream of water when mounted 96”(243.84cm) to 82”(208.28cm) from standing level. Shower head shall be supplied with self-adjusting 30 gpm (113.6 lpm) regulator to assure a constant flow and pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Shower head to be manufactured of type 304 stainless steel. Shower head shall deliver a minimum of 20”(50.8 cm) diameter pattern to the target area 60”(152.4 cm) above standing level. Shower units that provide improper flow pattern are not acceptable.

Encon Safety Products Model 01055005 includes 20 gpm shower head.

Encon Safety Products Model 01055007 includes 30 gpm shower head.

***Note:** Where hazardous materials that are injurious to the skin are used, a proper eyewash or eye/facewash installation with an emergency shower should be considered.

MATERIALS OF CONSTRUCTION:

SHOWERHEAD: Yellow ABS plastic shower head.

REGULATOR: Self-adjusting 30 gpm (113.6 lpm) regulator.

SUPPLY: 1” NPT

WEIGHT: 1 lbs (0.45 kgs)

