



1-800-283-6266

Phone: (713) 466-1449 Fax: (713) 466-1703

E-Mail: customerservice@enconsafety.com



FLOOR MOUNTED SHOWER

PART NUMBER: 01050204

SPECIFICATION:

Third party certified to ANSI Z358.1, the shower shall deliver 30 gpm (113.6 lpm) @ 30/70 psi (206.8/482.6 kPa) of flowing pressure. Unit shall provide a non-injurious stream of water for 15 minutes or longer. Unit shall be supplied with 1" stainless steel (SS) single motion activation stay open ball valve with SS ball. Shower shall include SS actuator with actuation graphic, type 304 schedule 40 stainless steel piping and 1/4" supply connection with flanged floor mounting plate for free-standing installation. Shower head shall be supplied with self-adjusting 30 gpm (113.6 lpm) regulator to assure a constant flow and pattern under 30/70 psi (206.8/482.6 kPa) hydraulic conditions. Shower head to be manufactured of UV resistant high visibility yellow ABS plastic. Shower head must deliver a minimum of 20" (50.8cm) diameter pattern to the target area 60" (152.4cm) above standing level. Shower units that provide improper flow pattern are not acceptable. Shower shall be Encon Safety Products Model 01050204.

MATERIALS OF CONSTRUCTION:

PIPING: Type 304 schedule 40 stainless steel.

VALVES: 1" stainless steel stay open ball valve with stainless steel ball and stainless steel pull rod assembly with actuation graphic.

HEAD: Yellow ABS plastic shower head.

REGULATOR: Self-adjusting 30 gpm (113.6cm) regulator assures a constant flow pattern under varying hydraulic conditions.

SUPPLY: 1 1/4" NPT

WEIGHT: 44 lbs (19.96 kgs)

***Note:** Where hazardous materials are used that are injurious to the skin, a proper eyewash or eye/facewash installation with the shower is recommended.

MODEL #	DESCRIPTION
01050204	Unit as Specified

